



**TECHINCAL SPECIFICATIONS**

- 1) **SHORELOC**® UNITS ARE MANUFACTURED IN ACCORDANCE WITH ASTM C90 AND C140 AND THE FOLLOWING CRITERIA:
  - A) CONCRETE UNIT WEIGHT 130 -150 LBS/CF
  - B) MINIMUM COMPRESSIVE STRENGTH - 4,000 PSI.
  - C) MAXIMUM ABSORPTION - 7 %
  - D) DIMENSIONAL TOLERANCE ± 1/8"

<b>SPECIFICATIONS</b>							
<b>BLOCK NUMBER</b>	<b>DIMENSION (in.)</b>			<b>BLOCK</b>		<b>UNIT COVERAGE SQ. FT.</b>	<b>OPEN AREA %</b>
	<b>H</b>	<b>W</b>	<b>L</b>	<b>UNIT WEIGHT LBS</b>	<b>SYSTEM WEIGHT LBS. PER SQ. FT.</b>		
<b>H-400 OC</b>	<b>4"</b>	<b>12"</b>	<b>16"</b>	<b>30-35</b>	<b>30-35</b>	<b>1.0</b>	<b>25</b>
<b>H-500 OC</b>	<b>5"</b>	<b>12"</b>	<b>16"</b>	<b>37-44</b>	<b>37-44</b>	<b>1.0</b>	<b>25</b>
<b>H-600 OC</b>	<b>6"</b>	<b>12"</b>	<b>16"</b>	<b>45-53</b>	<b>45-53</b>	<b>1.0</b>	<b>25</b>

**SHORETEC® L.L.C.**

510 O'NEAL LANE  
 Baton Rouge, Louisiana 70819  
 (225) 408-1444 - Phone  
 (225) 408-1445 - Fax  
 www.shorettec.com

Client:		Title:		No.		Date	Revision	By
		SHORELOC® SERIES BLOCK DETAILS						
Scale:	Drawn By:	File Name:	Project No:	Drawing No:				
N.T.S.	A. CASE			2				

DISCLAIMER  
 THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED BY SHORETEC, LLC AND TO THE BEST OF OUR KNOWLEDGE, ACCURATELY REPRESENTS THE SHOREBLOCK PRODUCT USE IN THE APPLICATIONS WHICH ARE ILLUSTRATED. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND ITS MANNER OF USE ARE THE SOLE RESPONSIBILITY OF THE USER. STRUCTURAL DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFIED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR THIS SPECIFIC PROJECT ONLY. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN CONFIDENCE AND AGREES THAT IT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART, NOR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF SHORETEC L.L.C.