



INSTALL 6" LONG SOD STAMPLE AT EACH CORNER AND 2' O.C. ALONG OUTER EDGE

**NOTES:**

1. CLEARING AND GRUBBING WITHIN THE DRIPLINE OF TREES TO BE PRESERVED. SHALL BE LIMITED TO SURFACE CLEARING AND GRUBBING TO A MAXIMUM DEPTH OF 2 INCHES USING HAND TOOLS.
2. EROSION CONTROL BLANKET MAY BE PLACED ON UNDISTURBED SOIL WITH MAXIMUM OF 1 1/2" MOWED PLANT STUBBLE.



38200 LA Hwy. 16  
Denham Springs, LA 70706  
1-800-575-7293  
www.shoretec.com

Client:		Title:		No.		Date	Revision	By
		<b>SHOREBLOCK® BD SERIES SCOUR PROTECTION AT TREES</b>						
Scale:	File Name:	Project No.:	Drawing No.:					
N.T.S.			24					

DISCLAIMER  
THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED BY SHORETEC® LLC AND TO THE BEST OF OUR KNOWLEDGE, ACCURATELY REPRESENTS THE SHORETEC® PRODUCT USE IN THE APPLICATIONS WHICH ARE ILLUSTRATED. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND ITS MANNER OF USE ARE THE SOLE RESPONSIBILITY OF THE USER. STRUCTURAL DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFIED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR THIS SPECIFIC PROJECT ONLY. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN CONFIDENCE AND AGREES THAT IT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART, NOR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF SHORETEC® L.L.C.